

## STUFEX<sup>®</sup> GEL FILLER

Filler in water-based gel

Rev. January 2014

### Applications

Quick-drying thixotropic filler with excellent filling properties to be used to fill raw timber or as a filler after the first coat of varnish. It is applied with a spatula to avoid leaving any lumps and, once completely dry, it can be varnished without sanding down. To be used only with coats of solvent-based varnish. Not to be used on exotic woods, particularly worn and/or split parquet, floating parquet and parquet impregnated with oil or wax.

### Technical data

#### PRODUCT IDENTIFICATION DATA

Appearance	Thixotropic gel
Conservation	In the original container kept tightly shut, avoiding low temperatures. Use preferably within 12 months.

#### APPLICATION DATA

Drying time	45-60 minutes approx. with 10-12% wood moisture content
How to apply	Spatula

*The above information applies to a temperature of 20°C and relative humidity of 60%. A different temperature and/or relative humidity can lead to variations in these data.*

### How to apply

*Ensure that the surface to be treated is perfectly clean and dry.*

Spread two coats with a spatula using cross-strokes, avoiding leaving any ridges or lumps.

The flooring can be varnished once the filler is completely dry, including without sanding down.

(Tools can be cleaned with paint thinner)

### Consumption

The ideal quantity to apply is

**about 25-30 m<sup>2</sup>/kg**

### Packaging

The product is supplied in tins of

5kg

### Warnings

The temperature, humidity and quantity applied can prolong drying time.

When handling avoid contact with the eyes or skin, wear suitable protective clothing because the product may cause irritation.

**The instructions provided in this document are consistent with the most recently available information on the development and use of our product. Because we have no control over the onsite use and application of the product, we may only be held liable for the quality of the product as supplied.**