

BESSEMER[®] UNITHIN

Universal thinner

2546-a November 2024

Description

Product type: Universal special thinner for Bessemer coatings.

Field of application BESSEMER UNITHIN is used for viscosity adjustment and as a cleaning thinner for the following Bessemer products:

- BESSEMER AMBOS
- BESSEMER AMBOS ULTRA
- BESSEMER RS GRUND
- BESSEMER VB SUPER
- BESSEMER METALLIC

The quantities added are generally 3-5%, depending on the product.

Packaging: 1 l, 5 l, 10 l

Technical data

Density: approximately 0.78 g/cm³ (20 °C)

Flash point: -18°C

Ignition temperature: 250°C

Viscosity: approximately 10s., DIN 4 mm flow cup (20°C)

Storage: Store in a cool place not prone to freezing. Seal partially used containers well. Store only in original containers and out of reach of children.

Special Notes

For detailed information on disposal, water hazard class, VbF and ADR/RID, please refer to the safety data sheet, available at <https://myamonn.amonncolor.com/>.

The information provided in this data sheet reflects the current state of technical knowledge and is intended for guidance only. The recommended systems and substrates are given as examples. Suitability must be assessed on a case-by-case basis. Should you have any questions, please contact our technical support. Liability is governed by our General Terms and Conditions of Sale and Delivery. This data sheet supersedes and replaces all previous editions.