

CLOE WOOD OIL

Natural oil for special maintenance of oiled/waxed parquet floors

3C77-a August 2022

Description

Product: CLOE WOOD OIL is a natural for the special maintenance of both oiled and waxed wooden floors that have been greyed and depleted by trampling. CLOE WOOD OIL cleans stubborn stains, enhances the tone, nourishes and regenerates wood to its original shine and water-repellency.

Applications: Suitable for the special maintenance of any wood treated with oil-wax.

Packaging: 1l and 5 l in metal containers

Technical Data

Specific weight: approx. 0.9 g/cm³, at +20 °C., depending on the shade

Flash point: 51 °C

Viscosity: approx. 50 s/ DIN cup 53211, 2 mm, at +20°C.

Drying time: depending on type of surface and the quantity applied approx. 4 – 8 hours. High air humidity and/or low temperatures slow down drying.

Odour: strong own smell of orange; odourless after drying

Storage: shelf life 5 years in original closed containers. Store at a cool temperature protected from frost (min 5 – 7°C). Close partially used tins carefully; if there is a particularly large air space transfer to smaller containers.

How to apply

General instructions: mix CLOE WOOD OIL well before using. Do not work at temperatures below +10°C (environment, surface or product).

Application advice: Pour or spray CLOE WOOD OIL on the floor and spread evenly with a dry spreader or with a cotton cloth, until the tone of the parquet is revived. We recommend applying a very thin layer. Wait at least 4/8 hours before walking on the surface. On completely transparent treatments, treated surfaces not exposed to light may yellow. To reduce this effect, do not cover treated parts for at least 5/7 days. Do not use on white floors. Do not use on the inside of furniture.

Consumption: 25- 30 m²/l, per coat, depending on the wood absorption.

Dilution: CLOE WOOD OIL is ready to use and does not need to be diluted.

Tool cleaning: with CLOE THINNER immediately after use. Alternatively, use soap and water.

Special instructions

Check the information in the safety data sheet. Danger of spontaneous combustion of soaked rags which must be kept in closed metal containers or immersed in water. Contains: D-limonene. Flammable liquid and vapours. Causes skin irritation. May cause allergic skin reaction. Toxic to aquatic organisms with long lasting effects. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/heated surfaces or other sources of ignition. No smoking. Keep container tightly closed. Wear protective gloves, eye and face protection. In case of skin irritation or rash: seek medical attention. In the event of contact with the skin or eyes, rinse immediately and carefully with water.

Even biocompatible, petroleum-free products must be kept away from children and must not be disposed of in waste water but must be disposed of according to local regulations. Do not swallow the product.

Disposal: Only dispose of perfectly clean containers at recycling centres. Do not dispose of soiled containers and material residues as domestic waste but at special waste collection centres. Do not dispose of the product and its residues into drains, surface water or soil.

TOTAL DECLARATION OF RAW MATERIALS

Orange terpene, natural pine, tung and linseed oils, lecithin, carnauba wax, ethyl alcohol, calcium resinate, clays, lead-free desiccants.

FREE FROM acrylic, polyurethane, vinyl and alkyd resins of petrochemical origin.

CLOE WOOD OIL

Natural oil for special maintenance of oiled/waxed parquet floors

3C77-a August 2022

TOTAL VOC CONTENT DECLARATION – Directive 2004/42/EC of the European Parliament

Definition of VOC (volatile organic compound): any organic compound having an initial boiling point of 250°C or less, measured at a standard pressure of 101.3 kPa.

	Subcategory	Type	Limit g/l*	VOC g/l
f	Non-film-forming impregnating agents for wood	A	700	<610 g/l

* maximum permitted VOC limit from 1/01/2010 according to Directive 2004/42/EC.

The above instructions are consistent with the most recent information on development and application techniques. Because we have no control over the on-site use and application of the products, we are solely responsible for their consistent quality. If in doubt, please request our technical advice.