

## HYDROLAC MARINE

Water-soluble polyurethane varnish for boats

3S51-a Rev. October 2020

### Applications

Water-based, single-component, anti-yellowing polyurethane varnish for varnishing parquet, interior wood flooring and coverings, recommended especially for boats. Hydrolac Marine is characterised by its extremely high resistance to abrasion and to staining by commonly used substances such as wine, coffee, detergents, etc.. It is quick drying, easy to use and odourless. The Ecolabel label certifies the product's low environmental impact.

### Technical data

Paint cycle:	monocomponent varnish cycle
Colour:	Transparent, colourless
Gloss:	matt (19 - 25 GLOSS)
Volumetric mass:	980 -1030 g/l
Viscosity at acceptance test:	52 sec +/- 2 sec (DIN 3)
Solid content in weight:	23 - 25 %
Drying:	<ul style="list-style-type: none"> <li>▪ Dust dry 20 -30 min</li> <li>▪ Sandable after 6-8h</li> </ul>
Overpainting:	Painting over after 6-8h
Storage:	At least 1 year in original container, well closed. Avoid low temperature. DO NOT ALLOW TO FREEZE.
Packaging:	See price list

*Data above indicated, are purely indicative, and refers to the matt finish varnish. They have been obtained with an application of 150 micron (20°C, relative humidity 65%). Different thickness and/or temperature and/or humidity might imply data variation.*

### Application notes

**Surface preparation:** The wood must be clean, free of dust and grease and the humidity must be lower than 12%, clean, free of dust and greasy substances (oil, wax, etc.), that could interfere with a perfect adherence of the paint.

**Product preparation:** mix the product well before use.

**Dilution:** The product is supplied ready-to-use. If necessary, dilute with 5% water maximum, shaking well the product during this operation.

**Application:** roll, brush, spray. In order to obtain best results, apply the following coats:

- **Traditional painting:** various coats of HYDROLAC, with intermediate sanding after 6-8 hours

## HYDROLAC MARINE

Water-soluble polyurethane varnish for boats

3S51-a Rev. October 2020

**Tool cleaning:** with water immediately after use.

**This paint satisfies conditions for UE ecological system ECOLABEL**

**Registration Number IT/044/002.**



**This information is based on the most recent state of the art information, development and application of our product. Since we have no influence on the application of this product, we can only guarantee its constant quality.**