

STUFEX® STUCCO VT

Single-component nitro filler

Rev. January 2014

Applications

Transparent liquid ideal for filling gaps, pores or imperfections in the wood. Stufex VT Filler is extremely practical and convenient to use compared to ready-prepared fillers whose colour never matches that of the surface.

Technical data

PRODUCT IDENTIFICATION DATA

Appearance Slightly thixotropic

Test viscosity (DIN 6) 45 +/- 3 sec

Conservation In the original container kept tightly shut, avoiding low temperatures. Use preferably within 12 months.

APPLICATION DATA

Drying time 30 minutes approx. with 12% wood moisture content

The above information applies to a temperature of 20°C and relative humidity of 60%. A different temperature and/or relative humidity can lead to variations in these data.

How to apply

PREPARATION

Mix Stufex VT filler with the sanding dust obtained from the wood to produce an even-textured paste (max 15 – 20% powder).

APPLICATION

Spread the paste on the item to be treated, covering all the imperfections, splits and gaps. Stufex VT Filler is extremely quick-drying and can be sanded down after just a few minutes, thus saving a great deal of time.

(Tools can be cleaned with paint thinner)

Packaging

The product is supplied in tins of

20kg – 10kg – 5kg

Warnings

When handling avoid contact with the eyes or skin, wear suitable protective clothing because the product may cause irritation.

The instructions provided in this document are consistent with the most recently available information on the development and use of our product. Because we have no control over the onsite use and application of the product, we may only be held liable for the quality of the product as supplied.