

BESSEMER[®] UNITHIN

2546-a May 2022

Description

Product: mixture of solvents; inflammable colourless liquid.

Use: BESSEMER UNITHIN is a thinner which is used to clean tools and adjust viscosity when applying BESSEMER AMBOS, BESSEMER AMBOS ULTRA, BESSEMER RS GRUND, BESSEMER VB SUPER and BESSEMER METALLIC. The dosage varies from 3% to 5% according to the product.

Packaging: 1 l, 5 l, 10 l, 30 l.

Technical data

Density: approx. 0.78 g/cm³, at +20 °C

Flash point: -18°C

Auto-ignition temperature: 250 °C

Viscosity: approx. 10 s (DIN 4 mm) at 20°C

Storage: Store at a cool temperature protected from frost. Close partially used tins carefully. Keep in the original containers only and out of the reach of children.

Special instructions

Read the instructions on the safety sheet. Ensure the workplace is well ventilated. Keep out of the reach of children. In the event of contact with the skin or eyes, rinse immediately and carefully with water.

Disposal: EWC and AVV (German waste regulations) classification: 14 06 03 (other solvents and solvent mixtures). Do not dispose of dirty containers or residues of material as domestic waste but at special waste collection centres. Only dispose of perfectly clean containers at recycling centres. Do not throw the product or its residues into the sewer system, into surface water or onto the soil.

VbF classification: A I.

ADR/RID: UN 1263 paint, class 3, II, hazardous for the environment

The above instructions are consistent with the most recent information on the development and use of our product. Because we have no control over the onsite use and application of the product, we may only be held liable for the quality of the product as supplied. If in doubt please contact our technical consultancy service.