

## LIGNEX<sup>®</sup> GARTEN AUFHELLER

Brightener for old, discoloured wood

3273-b January 2016

### Description

**Product:** LIGNEX GARTEN AUFHELLER is a product that brightens up wood that has turned grey over time, restoring its original natural colour.

**Applications:** for use on outdoor wood surfaces that have turned grey, such as garden furniture and fittings, decking etc.

**Packaging:** 0.75l and 2.5l in plastic containers.

### Technical data

**Specific weight:** approx. 1.0 g/cm<sup>3</sup> (+ 20°C)

**Viscosity:** thixotropic

**Flash point:** > 21°C

**Odour:** weak odour in its liquid state, odourless once dry.

**Storage:** 2 years in intact containers. Store at a cool temperature protected from frost. Close partially used tins carefully. Store away from food, drink and animal feed. Only store the original, intact containers and keep out of the reach of children.

**Drying time:** depending on the type of wood, the quantity applied and the atmospheric conditions, the product dries in about 12 hours.

### How to apply

**Application system:** brush. Apply a generous quantity of LIGNEX GARTEN AUFHELLER with a brush and leave it to act for about 30 – 60 minutes. Then wash down the surface with plenty of water and brush it energetically with stiff brush. Rinse the surface again to eliminate any product residues. A further application may produce an even better result.

**Application temperature:** do not use in temperatures below +5°C.

**Surface preparation:** remove all traces of dust from the surface to be treated also removing any old, poorly-adhering varnish layers. Before applying the treatment to the wooden surface, mask any acid-sensitive parts such as metal, marble, etc.

**Yield:** approx. 5m<sup>2</sup> a litre if two coats are applied.

**Dilution:** LIGNEX GARTEN AUFHELLER is ready for use. It must not be diluted.

**Over-painting:** once completely dry, the wood can be treated with one of suitable oils in the Garten range.

**Tool cleaning:** immediately after use, with water and detergent. Dispose of cleaning residues in an appropriate manner.

### Special instructions

Always take the relevant precautions for working with paint/varnish and follow the instructions in the safety sheet. LIGNEX GARTEN AUFHELLER contains oxalic acid. Harmful to the health if it comes into contact with the skin or is ingested. Store the product closed and keep out of the reach of children. During use wear suitable protective gloves. If any body parts have come into contact with the product wash them immediately with plenty of water and remove dirty garments immediately.

**European waste catalogue:** 08 01 15 (aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances). Do not dispose of with domestic waste, do not throw the product onto soil or into the sewer system.

**Water hazard class:** WGK 1 (self-classification): low hazard.

**VbF classification:** A I.

**ADR/RID:** UN 1263, paint and similar materials, 3, III.

*The above instructions are consistent with the most recent information on the development and use of our product. Because we have no control over the onsite use and application of the product, we may only be held liable for the quality of the product as supplied. If in doubt please contact our technical consultancy service.*