Version number 17 Printing date 23.04.2018 Revision: 23.04.2018

## SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: BESSEMER AMBOS GRUND
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Coating compound/ Surface coating/ paint

Coating material

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Amonn Coatings GmbH An der Landesbahn 7 A-2100 Korneuburg

Tel.: +43 2262 735 80 - Fax.: +43 2262 735 80-19

Distributor:

J.F. Amonn SRL/GmbH I-39100 Bolzano/Bozen

Via Altmann 12 Altmannstraße Tel.: +39 0471 904-911 - Fax.: +39 0471 910-449

· Informing department: E-Mail: verkauf@amonn.at

· 1.4 Emergency telephone number:

National Poisons Information Service (NPIS) In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

In N Ireland: Contact your local GP or pharmacist during normal hours; click here (www.gpoutofhours.hscni.net/)

for GP services Out-of-Hours. In Republic of Ireland: 01 809 2166

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Lia. 3 H226 Flammable liquid and vapour.

Aguatic Chronic 2 H411 Toxic to aguatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS09

· Signal word Warning

· Hazard statements

H226 Flammable liquid and vapour.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition P210

sources. No smoking.

Avoid release to the environment. P273 P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

(Contd. of page 1)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.04.2018 Version number 17 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	5-10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	5-10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	3-7%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	3-7%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	3-7%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxypropan-2-ol Flam. Liq. 3, H226; STOT SE 3, H336	3-7%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1.5-3%

· Additional information For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents

Water.

Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GE

Version number 17 Revision: 23.04.2018 Printing date 23.04.2018

Trade name: BESSEMER AMBOS GRUND

(Contd. of page 2)

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers:

Store in well closed containers in a cool, well ventilated area. Direct sunshine should be avoided.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

	control parameters
	ponents with limit values that require monitoring at the workplace:
7727	-43-7 barium sulphate, natural (5-10%)
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust
	36-4 n-butyl acetate (3-7%)
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-0	55-6 2-methoxy-1-methylethyl acetate (3-7%)

100-0	io-o z-inethoxy- i-inethylethyl acetate (5-
WEL	Short-term value: 548 mg/m³, 100 ppm
	Long-term value: 274 mg/m³, 50 ppm

Sk

#### 107-98-2 1-methoxypropan-2-ol (3-7%)

101 00 = 1 memerypropun = 01 (0 1 /o)			
WEL	Short-term value: 560 mg/m³, 150 ppm		
	Long-term value: 375 mg/m³, 100 ppm		
	Sk		

#### · DNELs

64742-95-	6 Solvent naphtha	(petroleun	ı), light	arom.
0 1	1 (		- CC ( -	44

0+1+2-33	047-42-33-6 Golvent naphtha (petroleum), nght arom.			
Oral	Long-term exposure, systemic effects	11 mg/kg bw/day (Ver)		
Dermal	Long-term exposure, systemic effects	25 mg/kg bw/day (Arb)		
		11 mg/kg bw/day (Ver)		
Inhalative	Long-term exposure, systemic effects	150 mg/m³ (Arb)		
		32 mg/m³ (Ver)		

(Contd. on page 4)

Printing date 23.04.2018 Version number 17 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

123-00-4	n-butyl acetate	(Contd. of pa
Oral	Long-term exposure, systemic effects	2 ma/ka hw/day (Ver)
Orai	Acute, systemic effects	2 mg/kg/day (Ver)
Dermal	Long-term exposure, systemic effects	
Demiai	Long-term exposure, systemic enects	
	Acute legal effects	6 mg/kg bw/day (Ver)
	Acute, local effects	11 mg/kg (Arb)
	Acute, systemic effects	6 mg/kg/day (Ver)
Innalative	Long-term exposure, systemic effects	300 mg/m³ (Arb)
		35.7 mg/m³ (Ver)
	Long-term exposure, local effects	600 mg/m³ (Arb)
		35.7 mg/m³ (Ver)
	Acute, systemic effects	300 mg/m³ (Arb)
		300 mg/m³ (Ver)
	Acute, local effects	600 mg/m³ (Arb)
		300 mg/m³ (Ver)
Hydrocar	bons, C9-C10, n-alkanes, isoalkanes	
Oral	Long-term exposure, systemic effects	300 mg/kg bw/day (Ver)
Dermal	Long-term exposure, systemic effects	
		300 mg/kg bw/day (Ver)
Inhalative	Long-term exposure, systemic effects	1,500 mg/m³ (Arb)
		900 mg/m³ (Ver)
Naphtha	(petroleum), hydrotreated heavy	<b>3</b> ( )
Oral	Long-term exposure, systemic effects	300 mg/kg bw/day (Ver)
Dermal	Long-term exposure, systemic effects	
Domina.	Leng term expectate, eyeterme enecte	300 mg/kg bw/day (Ver)
Inhalative	Long-term exposure, systemic effects	
minalative	Long term exposure, systemic enects	900 mg/m³ (Ver)
107-98-2	1-methoxypropan-2-ol	300 mg/m (101)
Oral	Long-term exposure, systemic effects	3.3 mg/kg bw/day (Ver)
Dermal	Long-term exposure, systemic effects	
		18.1 mg/kg bw/day (Ver)
Inhalative	Long-term exposure, systemic effects	369 mg/m³ (Arb)
mmarativo	Leng term expectate, eyeterme enecte	43.9 mg/m³ (Ver)
	Acute, local effects	553.5 mg/m³ (Arb)
1311-13-2	2 zinc oxide	300.0 mg/m (Alb)
Oral		0.83 ma/ka hw/day (Var)
Orai Dermal	Long-term exposure, systemic effects Long-term exposure, systemic effects	
Deiiiidi	Long-term exposure, systemic effects	
		83 mg/kg bw/day (Ver)
Inholati:	Long form oversaling alletonic off1-	
Inhalative	Long-term exposure, systemic effects	5 mg/m³ (Arb)
Inhalative		2.5 mg/m³ (Ver)
	Long-term exposure, systemic effects  Long-term exposure, local effects	_ ` '
PNECs	Long-term exposure, local effects	2.5 mg/m³ (Ver)
PNECs 123-86-4	Long-term exposure, local effects  n-butyl acetate	2.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0.	Long-term exposure, local effects  n-butyl acetate 18 mg/l (freshwater)	2.5 mg/m³ (Ver)
<b>PNECs 123-86-4</b> PNEC 0.	n-butyl acetate 18 mg/l (freshwater) 018 mg/l (Marine Water)	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0. 0.0 35	Long-term exposure, local effects  n-butyl acetate  18 mg/l (freshwater)  018 mg/l (Marine Water)  6.6 mg/l (sewage traetmant plant microc	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0. 0.0 35	n-butyl acetate 18 mg/l (freshwater) 018 mg/l (Marine Water)	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0. 0.0 35 0.3	Long-term exposure, local effects  n-butyl acetate  18 mg/l (freshwater)  018 mg/l (Marine Water)  6.6 mg/l (sewage traetmant plant microc	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0. 0.0 35 0.3 PNEC 0.0	Long-term exposure, local effects  n-butyl acetate 18 mg/l (freshwater) 018 mg/l (Marine Water) 6.6 mg/l (sewage traetmant plant micros	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0. 0.0 35 0.0 PNEC 0.6	Long-term exposure, local effects  n-butyl acetate 18 mg/l (freshwater) 018 mg/l (Marine Water) 6.6 mg/l (sewage traetmant plant microcate mg/l (sporadic release) 0903 mg/kg (soil)	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0.0 0.0 35 0.0 PNEC 0.0 0.0 0.0	Long-term exposure, local effects  n-butyl acetate 18 mg/l (freshwater) 018 mg/l (Marine Water) 6.6 mg/l (sewage traetmant plant microca) 36 mg/l (sporadic release) 0903 mg/kg (soil) 981 mg/kg (sediment, freshwater)	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)
PNECs 123-86-4 PNEC 0.0 35 0.5 PNEC 0.0 0.9 107-98-2	Long-term exposure, local effects  n-butyl acetate 18 mg/l (freshwater) 018 mg/l (Marine Water) 6.6 mg/l (sewage traetmant plant microcom mg/l (sporadic release) 0903 mg/kg (soil) 0981 mg/kg (sediment, freshwater) 0981 mg/kg (sediment, marine water)	2.5 mg/m³ (Ver) 0.5 mg/m³ (Ver)

Printing date 23.04.2018 Version number 17 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

	(Contd. of page 4)		
	100 mg/l (sewage traetmant plant microorganisms)		
	100 mg/l (sporadic release)		
PNEC	4.59 mg/kg (soil)		
	52.3 mg/kg (sediment, freshwater)		
	5.2 mg/kg (sediment, marine water)		
1314-1	3-2 zinc oxide		
PNEC	0.0206 mg/l (freshwater)		
	0.0061 mg/l (Marine Water)		
	0.1 mg/l (sewage traetmant plant microorganisms)		
PNEC	35.6 mg/kg (soil)		
117.8 mg/kg (sediment, freshwater)			
	56.5 mg/kg (sediment, marine water)		

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

- · Breathing equipment: Use breathing protection in case of insufficient ventilation.
- · Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed safety glasses.

9.1 Information on basic physical al General Information	nd chemical properties	
Appearance: Form: Colour: Odour: Odour threshold:	Fluid According to product specification Characteristic Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling rai	Not determined nge: >100 °C	
Flash point:	>23 °C	
Inflammability (solid, gaseous)	Not applicable.	
Ignition temperature:	>200 °C	
Decomposition temperature:	Not determined.	
Self-inflammability:	Product is not selfigniting.	

Version number 17 Printing date 23.04.2018 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

	(Contd. of page
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
Critical values for explosion: Lower:	0.6 Vol %
Upper:  Vapour pressure at 20 °C:	6.5 Vol % 5 hPa
Density at 20 °C     Relative density     Vapour density     Evaporation rate	1,35 - 1,40 g/cm3 Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: dynamic: kinematic at 20°C:	Not determined. 140 - 180 s (DIN 4mm)
· Solvent content: Organic solvents: VOC (EU)	32.8 % EU limit value for this product (cat. A/i): 500 g/l (2010). This product contains max 500 g/l VOC
Solids content: - 9.2 Other information	65.5 % No further relevant information available.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available. 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values tha	t are relevant for classification:	
64742-95-	6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	3,492 mg/kg (rat) (OECD-Prüfrichtlinie 401)	
Dermal	LD50	>3,160 mg/kg (rat) (OECD-Prüfrichlinie 402)	
7779-90-0	trizinc bi	s(orthophosphate)	
Oral	LD50	>5,000 mg/kg (rat)	
123-86-4 i	n-butyl ac	etate	
Oral	LD50	10,760 mg/kg (rat)	
Dermal	LD50	>14,000 mg/kg (rab)	
Inhalative	LC50/4 h	>23.4 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)	
Hydrocari	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Naphtha (	Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rat)	
		(Contd. on page 7	

Version number 17 Printing date 23.04.2018 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

		(Contd. of page 6	3)
Inhalative	LC50/4 h	>20 mg/l (rat)	
107-98-2 1-methoxypropan-2-ol		٦	
Oral	LD50	>5,000 mg/kg (rat)	٦
Dermal	LD50	>2,000 mg/kg (rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
  · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms

  12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
UN1263		
1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (Solvent naphtha (petroleum), light arom. trizinc bis(orthophosphate)), MARINE POLLUTANT PAINT		

(Contd. on page

Printing date 23.04.2018 Version number 17 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

Class		(Contd. of page
Class Label 3 Class Label ADR, Ill Label Label Label ADR, Ill Label L	· 14.3 Transport hazard class(es)	
IMDG  Class 3 Flammable liquids.  ATA  Class 3 Flammable liquids.  IATA  Class 3 Flammable liquids.  IATA  Class 3 Flammable liquids.  IA4 Packing group ADR, IMDG, IATA III  III  14.5 Environmental hazards: Substances: trizinc bis(orthophosphate), zinc oxiding features and tree)  Special marking (ADR): Symbol (fish and tree)  Special marking (ADR): Not applicable.  IA4.6 Special precautions for user  Kemler Number: 50 Kemler Number: 70 Kemler	ADR	
IMDG  Class Class Label  IATA  Class JaFlammable liquids.  Class Label  IATA  Class Label  Class Label  III  Class Label  III  14.4 Packing group ADR, IMDG, IATA  III  Product contains environmentally hazardo: substances: trizinc bis(orthophosphate), zinc oxid: Yes Symbol (fish and tree) The more representations for user In the more representations for user In the more representations for user In the more representation of the light of the li		
Class Label 3 IATA  Class Label 3 IATA  Class Class Class Clabel 3 Class Class Clabel 3 Class		3 (F1) Flammable liquids. 3
Label 3  IATA  Class 3 Flammable liquids. 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Product contains environmentally hazardous ubstances: trizinc bis(orthophosphate), zinc oxiding the substances of t	· IMDG	
Label 3  IATA  Class 3 Flammable liquids. 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Product contains environmentally hazardor substances: trizinc bis(orthophosphate), zinc oxid Yes Symbol (fish and tree)  Special marking (ADR): Symbol (fish and tree)  14.6 Special precautions for user Kemler Number: Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR  Excepted quantities (EQ): E1 Limited quantities (EQ): E2 Limited quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml  Transport category 3 Tunnel restriction code D/E  IMDG Limited quantities (EQ) 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging	¥2>	
Class 3 Flammable liquids.  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Product contains environmentally hazardous substances: trizinc bis(orthophosphate), zinc oxid Yes Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree)  14.6 Special precautions for user Kemler Number: Warning: Flammable liquids. 30 F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Excepted quantities (EQ): Limited quantities (EQ)  Excepted quantities (EQ) Transport category 3 Limited quantities (LQ)  Transport category 3 Transport category 3 Limited quantities (LQ)  Transport category 3 Transport category 3 Limited quantities (LQ)  LIMICAL RAINT, 3, III, ENVIRONMENTALL		3 Flammable liquids.
Class Label 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Product contains environmentally hazardor substances: trizinc bis(orthophosphate), zinc oxid Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)  14.6 Special marking (ADR): Symbol (fish and tree) Symbol (fish and tree)  14.6 Special precautions for user Kemler Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  17 Transport/Additional information: ADR Excepted quantities (EQ): E1 Limited quantities (EQ) Excepted quantities (EQ)  1 Transport category 3 Tunnel restriction code  IMDG Limited quantities (LQ) Excepted quantities (EQ)  5 L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 10 ml		3
Label 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Product contains environmentally hazardor substances: trizinc bis(orthophosphate), zinc oxid Yes Symbol (fish and tree) Symbol (fish and tree)  14.6 Special precautions for user Kemler Number: Warning: Flammable liquids. 30  EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Excepted quantities (EQ): E1 Limited quantities (LQ) 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 10 ml Transport category 3 Tunnel restriction code D/E  IMDG Limited quantities (EQ) 5L Code: E1 Maximum net quantity per inner packaging: 30 ml	3	
ADR, IMDG, IATA  111  14.5 Environmental hazards:  Marine pollutant:  Special marking (ADR):  Special precautions for user  Kemler Number:  EMS Number:  Stowage Category  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code  Excepted quantities (EQ):  Limited quantities (EQ)  Transport category  Tunnel restriction code  Limited quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Transport category  Tunnel restriction code  Limited quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Tunnel restriction code  Limited quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  UN 1263 PAINT, 3, III, ENVIRONMENTALL	· Class · Label	
substances: trizinc bis(orthophosphate), zinc oxid Yes Symbol (fish and tree) Symbol (fish and tree)  14.6 Special precautions for user Kemler Number: EMS Number: Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information:  ADR Excepted quantities (EQ): Limited quantities (EQ) Excepted quantities (EQ) Excepted quantities (EQ) Transport category Transport category Transport category Transport category Trunnel restriction code Limited quantities (LQ) Excepted quantities (LQ) Transport category Tunnel restriction code Limited quantities (LQ) Excepted quantities (LQ)  Transport category Tunnel restriction code Limited quantities (LQ) Excepted quantities (LQ)  Transport category Tunnel restriction code Limited quantities (LQ) Excepted quantities (LQ)  Limited quantities (LQ)  Limited quantities (LQ)  Excepted quantities (LQ)  Limited quantities (LQ)  LIMIC Code: E1  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 10 ml  Maximum net quantity per outer packaging: 10 ml	· 14.4 Packing group · ADR, IMDG, IATA	III
Marine pollutant: Special marking (ADR): Special marking (ADR):  14.6 Special precautions for user Kemler Number: EMS Number: Stowage Category  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information:  ADR Excepted quantities (EQ): Limited quantities (EQ) Excepted quantities (EQ) Transport category  Tunnel restriction code  IMDG Limited quantities (LQ) Excepted quantities (EQ)  Transport category  Tunnel restriction code  IMDG Limited quantities (LQ) Excepted quantities (EQ)  Transport category  Tunnel restriction code  UN 1263 PAINT, 3, III, ENVIRONMENTALL	· 14.5 Environmental hazards:	
Special marking (ADR):  14.6 Special precautions for user Kemler Number: Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Excepted quantities (EQ): Limited quantities (EQ) Excepted quantities (EQ) Transport category Tunnel restriction code  IMDG Limited quantities (LQ)  Excepted quantities (LQ)  Transport category  Implication  Symbol (fish and tree)  Warning: Flammable liquids.  30 F-E,S-E A  Not applicable.  E1  Code: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 100  ml  Transport category  IMDG Limited quantities (LQ) Excepted quantities (EQ)  UN 1263 PAINT, 3, III, ENVIRONMENTALL	· Marine pollutant:	Yes
EMS Number: Stowage Category  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code  Not applicable.  Transport/Additional information:  ADR Excepted quantities (EQ): Limited quantities (LQ) Excepted quantities (EQ)  Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml  Transport category Tunnel restriction code  IMDG Limited quantities (LQ) Excepted quantities (EQ)  IMDG Limited quantities (EQ)  Excepted quantities (EQ)  UN "Model Regulation":  UN 1263 PAINT, 3, III, ENVIRONMENTALL	· Special marking (ADR):	Symbol (fish and tree)
of Marpol and the IBC Code  Transport/Additional information:  ADR  Excepted quantities (EQ):  Limited quantities (EQ)  Excepted quantities (EQ)  Excepted quantities (EQ)  Transport category  Tunnel restriction code  IMDG  Limited quantities (LQ)  Excepted quantities (EQ)  Tode: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 100  ml  SL  Code: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 30 ml  Maximum net quantity per outer packaging: 100  ml  UN 1263 PAINT, 3, III, ENVIRONMENTALL	<ul> <li>14.6 Special precautions for user</li> <li>Kemler Number:</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	30 F-E, <u>S-E</u>
Transport/Additional information:  ADR Excepted quantities (EQ): Limited quantities (LQ) Excepted quantities (EQ)  Excepted quantities (EQ)  Excepted quantities (EQ)  Transport category Tunnel restriction code  IMDG Limited quantities (LQ) Excepted quantities (EQ)  Excepted quantities (LQ)  Excepted quantities (LQ)  Excepted quantities (EQ)  UN 1263 PAINT, 3, III, ENVIRONMENTALL	· 14.7 Transport in bulk according to An	
ADR Excepted quantities (EQ): Limited quantities (LQ) Excepted quantities (EQ)  Excepted quantities (EQ)  Code: E1  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml  Transport category 3 Tunnel restriction code  D/E  IMDG Limited quantities (LQ) Excepted quantities (EQ)  Excepted quantities (EQ)  Code: E1  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml  UN 1263 PAINT, 3, III, ENVIRONMENTALL	•	
Transport category 3 Tunnel restriction code D/E  IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml  UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALL	· ADR · Excepted quantities (EQ): · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100
• Limited quantities (LQ) • Excepted quantities (EQ)  • Excepted quantities (EQ)  — Maximum net quantity per inner packaging: 30 ml  — Maximum net quantity per outer packaging: 100  — ml  • UN "Model Regulation":  UN 1263 PAINT, 3, III, ENVIRONMENTALL	· Transport category · Tunnel restriction code	3
· UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALL	· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100
	· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL

Version number 17 Printing date 23.04.2018 Revision: 23.04.2018

Trade name: BESSEMER AMBOS GRUND

(Contd. of page 8)

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGÚLAŤION (EĆ) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations
- · Technical instructions (air):

Class	Share in %
1	0.2
III	10.2
NK	22.5

- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing data specification sheet: Environment protection department.
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.